

## SPECIFICATION TABLE

SR.NO	P	ARAMETER	SPECIFICATION								
1	Туре		Three Pin integrally moulded Plug without connector								
2	V/A Rating		16 Amp,250 V ac								
3	Insulation Resist	ance at 500 V DC	100 M Ohms Min.								
4	H.V.Break Down	Test(For 1-Minute)	1.5 KV AC.								
5	Permissible Tem	p. With/Without Load	0°C TO 70°C								
6	Length (L), Mete	rs	As per requirement, Standard = 1.5								
7	MATERIAL	(a) Cable	PVC								
		(b) Conductors	Copper								
		(c) Conductor Size	1.50 Sq.mm								
		(d) Contacts	Brass, Nickel Plated								
8	Reference Stand	ard	IS-1293,IEC-884,IEC-799								

Note: 1) Plug & connector shapes are subject to change without notice

- 2)  $\ \ X'$  is denoted for the required wire length.
- 3) ISI and CE on customer demand.

## ORDERING CODE TABLE

SR.NO.	CODE	DESCRIPTION						
1	EMC-5150/X-MT	Without Tinned						
2	EMC-5150/X-MT-TN	With Tinned						

								APP	07.04.08		PBM		_	•	_		Dlati	- 4 1/		ive Stee	
								СНК						X			Plot E-4, Kagal Five Star MIDC, Kagal, Kolhapur, MH - 416236, India				
								DRN	07.04.08		UAJ		ELCOM Elcom Inter				national Pvt. Ltd.				
REV		IS		WAS	DATE	SIGN	APP.	BY	DATE		SIGN	www.elcom-in.com									
UNSP.TOLERANCE DI			DIMNS. IN	WT(Gm)	SCALE:-		PROJECTION		SHEET	DRAWING NUMBER											
OVER	-	1	10	mm	Max.		NTS.			4										DEVICION	
UP TO	1	10	-	Moulding.	plating details as per Bill of Material				$\neg + \neg \rightarrow ($	<del>                                    </del>		PE	_	ЕΙМΙ	c	9	_	1	5	REVISION	
±	0.2	0.3	0.5		I colour is Black, GF:Glass filled.								<u> </u>	LIVI C	٠	9	٥	1	$\perp$	0	

F:ENG-08.00

Note: Technical specifications are subject to change without prior notice