



Power Distribution Unit

Product code/Part code: E03-C36YF

Specification sheet:

Input

| | |
|----------------------|--|
| • Voltage: | 3 Φ , 250 VAC (P-N) 440 VAC (P-P) |
| • Frequency: | 50Hz/60Hz (as per supply input) |
| • Power in plug type | 32A 5 pin Industrial plug IP44(3P+N+E) |
| • Power cord : | FRLS, 6 sq.mm, 5 core, 3 meter with 32A 5 pin rewirable industrial plug IP44(3P+N+E) |
| • Input current: | 32A |

Output

| | |
|----------------------------|---------------------------------|
| • Voltage: | 1 Φ , 250VAC |
| • Frequency: | 50Hz/60Hz (as per supply input) |
| • Power out socket type: | IEC-C13 & IEC-C19 outlet |
| • Current operating range: | 32A per phase |

Features

- Rack-mountable
- 0U Vertical mounting
- Single input power source
- Protection with per phase single pole 32A “D” curve MCB with safety guard
- With per MCB Green LED indicator
- With digital ammeter
- Internal wiring with Uni-nyvin cable
- Total no. of outlets : 36nos[IEC-C13 lockable outlet =10nos/Phase & IEC-C19 lockable outlet =2nos./Phase]
- With mounting bracket spare =2nos.
- With external earthing provision.
- Reference standard :- IEC 62368-1

Mechanical

- Dimensions(L x W x H): (1650 x 65 x 60)mm
- Weight:approx. 6.3Kg
- Mounting : 1625mm
- Button mount: 1500mm
- Colour: RAL 9005
- Finish: Texture

Environmental requirements

- Operating temperature: 0 -45°C (Extended up to 60°C)
- Humidity: 0 – 95 % RH non-condensing

Compliance marking

- CE
- RoHS

