

Smart Power Distribution Unit

Product Code/Part Code: EAM-S636L-DE3JSVX

Specification Sheet:

Input

Voltage:	1Φ, 230-250VAC
Frequency:	50 Hz / 60Hz
Input Plug:	1Ф, 32 Amps, IEC 60309(P+N+E), 250VAC
Cord Length:	3 meters
Input Current:	32 Amps

Output

Voltage:	230-250VAC
• Frequency:	50Hz / 60Hz
Receptacles Configuration:	Hybrid Receptacles 5 in 1 Combo (C13/C19/C21/C15/C15A) (36 Nos.)
 Current Operating range: 	32 Amps

Features

- Aggregate Current Monitoring: Monitors the aggregate / Total current flowing through the device.
- Monitors and Tracks Aggregate power consumption.
- Conforms to CLASS 1 metering accuracy.
- Strip/PDU Level Metering of electrical parameters: Voltage (V), Current (I), Energy (kWh) Power (kVA, kW), Power factor (cos Φ).
- Threshold settings for input current with warning LED on the front panel and Buzzer alarm.
- 1.77" TFT Color LCD to display electrical parameters and PDU information
- Networking: Dual Ethernet Ports –10/100Mbps and 10/100/1000Mbps
- Provision to connect Elcom Make Temperature Humidity Sensors.
- Hot Swappable Controller
- Circuit Breaker trip detection.
- Firmware upgrades can be performed through a Web browser.
- Total No. of Receptacles: 36- Hybrid Receptacles 5 in 1 Combo (C13/C19/C21/C15/C15A) (36 Nos.)
- Branch Circuit Protection: Two (2) X 16A Hydraulic Magnetic Circuit Breakers(A) with circuit level current monitoring.



User Interface:

Integrates with any DCIM System through SNMP or MODBUS RTU/ MODBUS TCP

Interface and Protocol Support

- HTTP, HTTP(s)
- SNMP v1, v2c, v3
- MODBUS RTU & MODBUS TCP
- FTP
- DHCP
- IPV4, IPV6 Support
- Telnet (CLI)
- NTP
- SMTP
- Syslog
- LDAP
- RADIUS
- TACACS+
- TLS 1.2 supported.

Mechanical

- Dimensions (L x W x H): 1500mm x 75mm x 75mm
- Weight: Approx. 7.8 KgMounting: 1193.50mm
- Display/control panel: 1.77" TFT Color Display
- Color: RAL 9005Finish: Fine texture

Environmental Requirements

- Operating temperature: 0 45°C (Extended up to 60°C)
- Humidity: 0 95 % RH non-condensing

Conformance

Environmental Compliance

CE



Product Drawing

