



## Power Distribution Unit

Product code/Part code: EBP-S424P-LEX36VX

### Specification sheet:

---

#### Input

• Voltage:	1 $\Phi$ , 100-120VAC
• Frequency:	50Hz / 60Hz (as per supply input)
• Power in socket type:	20A ENP-LD5-20 Nema plug
• Power cord :	14 AWG 3 core 3.0 meter with rewirable 20A ENP-LD5-20 Nema plug
• Input current:	20A

#### Output

• Voltage:	1 $\Phi$ , 100-120VAC
• Frequency:	50Hz / 60Hz (as per supply input)
• Power out socket type:	ENO-1112-X, snap mounting outlet, 5-20R, Nema 20A 125VAC
• Current operating range:	20A

#### Features

- Rack-mountable
- Vertical mounting
- Single input power source
- With single pole 20A Hydraulic magnetic circuit breaker 1 no.
- Total no. of outlets: 24 [ENO-1112-X, snap mounting outlet, 5-20R Nema 20A 125VAC]

#### Mechanical

- Dimensions (L x W x H): 1375mm x 50mm x 70mm
- Weight: Approx. 4 Kg
- Mounting: 1350mm
- Color: RAL 9005
- Finish: Texture

#### Environmental requirements

- Operating temperature: 0 – 45°C (Extended up to 65°C)
- Humidity : 0 – 95 % RH non-condensing

#### Conformance

#### Approvals

- cULus

#### Marking

- CE
- cULus

#### Environmental Compliance

- RoHS

Product drawing

