



Power Distribution Unit

Product code/Part code: EBP-S610C-DGXFUHX

Specification sheet:

Input

• Voltage:	1 Φ , 120VAC
• Frequency:	50Hz/60Hz (as per supply input)
• Power in socket type:	IEC 60309 32Amp rewirable Industrial plug IP44 (2P+E)
• Power Cord:	Power cord 10 AWG,3 core 4 mtr. with IEC 60309 32Amp Industrial plug IP44 (2P+E)
• Input current:	32A

Output

• Voltage:	1 Φ , 120VAC
• Frequency:	50Hz/60Hz (as per supply input)
• Power out socket type:	IEC C13 outlet
• Current operating range:	32A

Features

- 19" Rack mountable
- 1U Horizontal mounting
- Single input power source
- Protection with single pole 16A Hydraulic magnetic circuit breaker=2nos
- Total no. of outlets: 10nos [EMO-13(Bank of 3 nos.IEC C13)outlet=2 nos. & EMO-12(Bank of 2 nos.IEC C13)outlet=2 nos.]

Mechanical

- Dimensions (L x W x H):[482.6mm(19.00") x 55.00mm(2.17") x 75mm(2.95")]
- Weight: Approx. 2.7Kg
- Button mounting: 465mm(18.30")
- Color: Ral 9005
- Finish: Texture

Environmental requirements

- Operating temperature: 0 – 45°C (Extended up to 65°C)
- Humidity: 0 – 95 % RH non-condensing



Conformance

Approvals

- cULus

Marking

- CE
- cULus

Environmental Compliance

- RoHS

Product drawing:

