



## Power Distribution Unit

Product code/Part code:EBP-T924C-GEX7QX

### Specification sheet:

#### Input

• Voltage:	3 $\Phi$ , 250VAC (Phase-Neutral) 440VAC (Phase-Phase)
• Frequency:	50Hz/60Hz (as per supply input)
• Power in socket type:	63A 5 pin Industrial plug
• Power cord:	6 AWG 5core 3 meter with rewirable 63A 5 pin Industrial plug.
• Input current:	63A

#### Output

• Voltage:	1 $\Phi$ , 250VAC
• Frequency:	50Hz/60Hz (as per supply input)
• Power out socket type:	IEC C13 & IEC C19 Outlet
• Current operating range:	63A per phase

#### Features

- Vertical mounting
- Single input power source
- Protection with per phase single pole 16A Hydraulic magnetic circuit breaker =4nos.  
Total no. of outlet: 24nos. [EMO-11(IEC C-13) outlet = 4nos. per phase & EMO-18(IEC C-19) outlet=4nos. per phase]

#### Mechanical

- Dimensions (L x W x H): 1425.0mm(56.10") x 90.0mm(3.54") x 80.0mm(3.15")]
- Weight: Approx. 6.5Kg
- Mounting system :1400.0(55.12") , Button mounting : 1225.0(48.23")
- Color: RAL 9005
- Finish: Texture

#### Environmental requirements

- Operating temperature: 0 - 45°C (Extended up to 65°C)
- Humidity: 0 – 95 % RH non-condensing



## Conformance

### Approvals

- cULus

### Marking

- CE
- cULus

### Environmental Compliance

- RoHS

Product drawing:

