



Power Distribution Unit

Product code/Part code: E03-C18YE

Specification sheet:

Input

• Voltage:	3 Φ , 250VAC (P-N) 440VAC (P-P)
• Frequency:	50Hz/60Hz (as per supply input)
• Power in socket type:	32A 5 pin Industrial plug IP44(3P+N+E)
• Power cord:	FRLS, 6 sq.mm, 5 core, 3 meter with 32A 5 pin rewirable industrial plug IP44(3P+N+E)
• Input current:	32A

Output

• Voltage:	1 Φ , 250VAC
• Frequency:	50Hz/60Hz (as per supply input)
• Power out socket type:	IEC C-13 & IEC C-19 Outlet
• Current operating range:	32A per phase

Features

- 0U, Vertical mounting
- Single input power source
- With per phase 32A single pole “D” curve MCB with safety guard
- With per MCB LED power indicator
- Internal wiring with Uni-nyvin cable
- With digital ammeter
- Total no. of outlet: 18nos. [IEC-C13 lockable outlet =3nos/Phase & IEC-C19 lockable outlet =3nos./Phase]
- With External Earthing provision
- With mounting bracket spare =2nos.
- Reference standard :- IEC 62368-1

Mechanical

- Dimensions (L x W x H): (1500 x 55 x 60)mm
- Mounting: 1475mm
- Button mounting: 1000mm
- Weight: approx. 5.5Kg
- Color: RAL 9005
- Finish: Texture

Environmental requirements

- Operating temperature: 0 – 45°C (Extended up to 60°C)
- Humidity: 0 – 95 % RH non-condensing

Compliance marking

- CE
- RoHS

