



## Power Distribution Unit

### Product Code/Part Code: E03-C36NB

#### Specification sheet:

---

#### Input

• Voltage:	3 $\Phi$ , 250 VAC (P-N) 440 VAC (P-P)
• Frequency:	50Hz/60Hz(as per supply input)
• Power in socket type:	32A 5 pin Industrial plug IP44(3P+N+E)
• Power cord:	FRLS, 6 sq.mm, 5 core, 3 meter with 32A 5 pin rewirable industrial plug IP44(3P+N+E)
• Input current:	32Amps

#### Output

• Voltage:	1 $\Phi$ , 250VAC
• Frequency:	50Hz/60Hz(as per supply input)
• Power out socket type:	IEC-C13 & IEC-C19 outlet
• Current operating range:	32Amps per phase

#### Features

- Rack-mountable
- 0U Vertical mounting
- Single input power source
- Protection with per phase single pole 32A “D” curve MCB with safety guard
- With per MCB green LED Indicator
- Internal wiring with Uni-nyvin cable
- Total no. of outlets: 36nos.[IEC-C13 lockable outlet =8nos. per phase  
&IEC-C19 lockable outlet =4nos.per phase]
- With mounting bracket spare =2nos.
- With external earthing provision.

#### Mechanical

- Dimensions(L x W x H): (1800 x 55 x 60)mm
- Weight: approx.6.2Kg
- Mounting: 1775mm
- Button mounting : 1650mm
- Color: RAL 9005
- Finish: Texture

#### Environmental requirements

- Operating temperature:0 – 45°C (Extended up to 60°C)
- Humidity: 0–95 % RH non-condensing

#### Compliance marking

- CE
- RoHS

